



MORBARK®

MADE FOR **MORE** TO KEEP PACE WITH **YOU**



**EEGER
BEEVER**

1215 BRUSH CHIPPER

With its power and easily transportable design, the compact and economical **Eger Beaver 1215** chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.

The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.

FEATURES AND BENEFITS

- The 18" (45.7 cm) diameter single top feed wheel easily climbs over material, reduces drag and increases chipping efficiency.
- 360° swivel discharge puts chips right where they're needed without removing the brush chipper from the tow vehicle.
- TorqMax™ Top Feed Wheel Compression system with spring-assisted down pressure generates more than 3,200 lb/ft (4,338 Nm) of material pulling force.
- Drive belt inspection cover provides easy access for drive system maintenance.
- The 60" wide x 31" high (152.4 x 78.7 cm) chute opening and 15" wide x 12" high (38.1 x 30.5 cm) throat opening allows for easy feeding of branchy material and reduced saw labor.



MORBARKDEALERS.COM



MORBARK®



EEGER BEEVER

1215 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 12/11/18

| GENERAL | US | METRIC |
|---------------------------------|---------------------|-------------------------|
| Height | 9' | 2.74 m |
| Width | 5'11" | 1.8 m |
| Length (transport) | 15'4" | 4.67 m |
| Length (operating) | 17'3" | 5.26 m |
| Gross weight (approximate) | 4,900 lb | 2,223 kg |
| Suspension | 7,000 lb Torflex | 3,175 kg Torflex |
| Infeed opening (height x width) | 31" x 60" | 78.7 x 152.4 cm |
| Throat opening (height x width) | 12" x 15" | 30.5 x 38.1 cm |
| Drum (width x diameter) | 14.2" x 21.4" | 36.2 x 54.3 cm |
| Engine | CAT, Perkins or PSI | |
| Horsepower | 49–89 HP | 36.5–66.4 kW |
| Fuel capacity | 24.5 gallons | 92.7 L |
| Hydraulic capacity | 17 gallons | 64.4 L |
| Frame | 8.2 lb, 6" channel | 3.7 kg, 15.2 cm channel |
| Tires | (2) 235/80R16 | |
| Hitch | 2.5" Pintle | 6.4 cm Pintle |

EQUIPMENT HIGHLIGHTS

- 21.375" (54.3 cm) diameter x 14.25" (36.2 cm) wide staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system
- Reversing automatic feed system
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
- Fuel tank gauge and shut-off valve
- Hydraulic tank shut-off valve, drain plug, sight gauge and clean-out cover
- Live hydraulics; ball valve, pump, motor and control valve
- Tube and support pad to mechanically raise and lower feed wheel using the drawbar jack
- 5" x 3" (12.7 cm x 7.6 cm) tubular steel telescoping drawbar with two 12" (30.5 cm) extensions

OPTIONS INCLUDE

- ChipSafe® Operator Safety Shield
- Bottom Bump Bar
- Cone Holder
- Chocks/Chock Holder
- Folding Infeed Tray
- Custom Paint and Logo Packages
- Spare Tire and Mount
- Strobe Light
- Pusher Paddle
- Infeed Curtain
- Rear Jacks

