



# MORBARK

MADE FOR **MORE** TO KEEP PACE WITH **YOU**



**EGER  
BEEVER**

# 1922 BRUSH CHIPPER

Ideal for residential tree services, vegetation management, lot and land clearing, maintenance contractors and municipalities, this chipper combines Morbark strength in a more compact design.

The **Eger Beaver 1922** weighs in at less than 10,000 lb (GVWR), eliminating the need for additional transport licensing requirements. (Dependent on options chosen.)

## FEATURES AND BENEFITS

- Bearing-style yoke pivot assembly with TorqMax™ drive and Variable Force™ down pressure system increases down pressure efficiency by 25%.
- Oversized perimeter opening with large throat opening, radius infeed walls and straight flow through infeed design increases efficiency while reducing infeed wear.
- Infeed is made with 7-gauge (5 mm), XF-100 sides and .375" (10 mm) thick, XF-100 floor to increase material tensile strength with lighter weight components.
- The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.
- 7-gauge split fuel and hydraulic reservoirs with shut-off valves reduce risks of vibration damage and cross-contamination while allowing for easy maintenance.



[MORBARKDEALERS.COM](http://MORBARKDEALERS.COM)



# MORBARK



# EEGER BEEVER

# 1922 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 12/11/18

GENERAL	US	METRIC
Height	9'4"	2.84 m
Width	7'8"	2.34 m
Length	18'3"	5.56 m
Gross weight (approximate)	9,550 – 11,500 lb	4,332 – 5,216 kg
Suspension	10,000 lb Torflex	4,536 kg Torflex
Infeed opening (height x width)	36" x 59"	91.4 x 149.9 cm
Throat opening (height x width)	19" x 21.3"	48.3 x 54 cm
Drum (width x diameter)	23.5" x 37.4"	59.7 x 94.9 cm
Engine	CAT, GM or Perkins	
Horsepower	165 – 174 HP	123 – 129.8 kW
Fuel capacity	44 gallons	166.6 L
Hydraulic capacity	26 gallons	98.4 L
Frame	8.2 lb, 6" channel	3.7 kg, 15.2 cm channel
Tires	(2) 235/75Rx17.5	
Hitch	2.5" Pintle	6.4 cm Pintle

## EQUIPMENT HIGHLIGHTS

- Four dual-edged knife staggered-pocket drum with removable knife holders, dual-sided, chambered air impeller system and controllable air flow vents
- Top 20.5" (52.1 cm) wide horizontal feed wheel equipped with serrated teeth and knife bars
- 360° manual crank swivel discharge with adjustable height and chip deflectors
- Live hydraulic system including: ball valve, pump, motor, and valve bank with additional preplumbed valve section for installation of an aftermarket winch package
- 4" x 6" (10.2 x 15.2 cm) tubular steel fixed-length drawbar and 0.375" (1 cm) thick safety chains with clasp hooks
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment

## OPTIONS INCLUDE

- ChipSafe® Operator Safety Shield
- Winch Package: heavy-duty, 5,000 lb (2268 kg) pull capacity with rope and 10' (3 m) chafe guard
- Custom Paint and Logo Packages
- Bottom Bump Bar
- Hydraulic Swivel Discharge
- Cone Holder
- Spare Tire and Mount
- Folding Infeed Tray
- Flow Control
- Axle Options Available
- Strobe Light
- Infeed Curtain
- Pusher Paddle
- Front and Rear Stabilizers

