



# MORBARK

With its large capacity and high-production volume reduction capabilities, this chipper is perfect for residential tree services, vegetation management, lot and land clearing, maintenance contractors and municipalities.

The **Eger Beaver 2131** boasts a huge list of options to customize the machine as well as more standard features than any other chipper in its class.

The 2131 is also available tracked for right of way clearing, highway cleanups and hard-to-reach areas requiring a self-propelled unit for material access. An optional loader also is available.



**MADE FOR MORE TO KEEP PACE WITH YOU**



## EEGER BEEVER

# 2131

## BRUSH CHIPPER

### FEATURES AND BENEFITS

- The unit can be outfitted with a four- or six-cylinder diesel engine and choice of single or tandem axle.
- The TorqMax™ dual feed wheel compression system provides more than 7,500 lb/ft (10,169 Nm) of material pulling force.
- The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 10,000 lb (4,536 kg) of perpetual down pressure.
- The dual-sided, chambered air impeller system with controllable air flow vents increases chip-throwing velocity and easy discharge of light, leafy material.
- The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum performance.



[MORBARKDEALERS.COM](http://MORBARKDEALERS.COM)



# MORBARK

**EEGER  
BEEVER**

# 2131 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 10/30/18

GENERAL	US	METRIC
Height	9'6"	2.9 m
Width	7'7"	2.31 m
Length	21'2"	6.45 m
Gross weight (approx., single axle)	11,000 lb	4,990 kg
Gross weight (approx., tandem axle)	12,200 lb	5,534 kg
Suspension (single axle)	(1) 10,000 lb Torflex	(1) 4,536 kg Torflex
Suspension (tandem axle)	(2) 8,000 lb Torflex	(2) 3,629 kg Torflex
Infeed opening (height x width)	36" x 59"	91.4 x 149.9 cm
Throat opening (height x width)	20.5" x 31"	52.1 x 78.7 cm
Drum (width x diameter)	23.5" x 37.4"	59.7 x 94.9 cm
Engine	CAT, GM or Perkins	
Horsepower	147–275 HP	109.6–205 kW
Fuel capacity	60 gallons	227.1 L
Hydraulic capacity	41 gallons	155.2 L
Frame	2" x 6" Tubular	5.1 x 15.2 cm Tubular
Tires	235/75Rx17.5	
Hitch	2.5" Pintle	6.4 cm Pintle

## EQUIPMENT HIGHLIGHTS

- 23.5" wide (59.7 cm) x 37.375" (94.9 cm) diameter, four dual-edged knife staggered-pocket drum with removable knife holders, dual-sided, chambered air impeller system and controllable air flow vents
- Dual horizontal feed wheels with TorqMax™ top feed wheel compression system, hydraulic lift assist and Variable Force™ constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle
- Live hydraulic system including: ball valve, pump, motor, and valve bank with additional preplumbed valve section for installation of an aftermarket winch package
- 360° manual height-adjustable discharge
- Direct-drive bottom feed wheel

## OPTIONS INCLUDE

- ChipSafe® Operator Safety Shield
- Winch Package: heavy-duty, 5,000 lb (2268 kg) pull capacity with rope and 10' (3 m) chafe guard
- Custom Paint and Logo Packages
- Bottom Bump Bar
- Hydraulic Swivel Discharge
- Cone Holder
- Spare Tire and Mount
- Folding Infeed Tray
- Flow Control
- Axle Options Available
- Infeed Curtain
- Strobe Light
- Pusher Paddle
- Front and Rear Stabilizers

