

HARD HITTING RELIABILITY PERIOD.



INTRODUCING LABOUNTY MOUNTED BREAKERS

The all new Labounty breaker line is designed for all day, everyday use in the most demanding applications. With heavy-duty housing designs and the latest technologies standard on most models, these breakers are destined to become the tool of choice for primary and secondary demolition, trenching, tunneling and boulder breaking.



Heavy-duty housing for enhanced durability under the toughest of conditions

Oil-fired Design Less Wear Compared to Gas Fired Designs

Auto-Lubrication System Increases Bushing Life by Automatically Providing Grease to the Hammer*

Data Logger Tracks Use of the Hammer and Provides Service Interval Status and Accumulated Working History

Fixed Impact Energy Valve Adjusts Blow Rate With Hydraulic Flow To Provide Consistent Impact

Energy Selectable Stroke Enables User To Adjust Blow Rate According To The Application

Accumulator Protects Carrier And Maximizes Impact Energy And Blow Rate

Vibration Dampening Tie Rods Helps Extend Tie Rod Life By Preventing Loosening

User Selectable Auto Shut Off Prevents Blank Firing To Extend Breaker Life*

*not available on the LMB1308



Ft. Lb Class	1200	2500	3500	5000	8000	11000	13000
BPM	500-1700	540-920	430-790	450-750	370-630	400-560	370-530
Weight (lbs)	1110	2400	3090	3880	5290	7450	10470
Tool Dia. (In)	3.54	4.53	4.92	5.31	5.59	6.54	7.48
Carrier Range (MT)	5-13	12-20	16-26	21-30	26-40	34-55	43-80
Flow Range (GPM)	13-40	24-34	32-48	37-53	42-66	66-92	74-100
Pressure Range (PSI)	1450-2030	1960-2105	2030-2320	1960-2105	2175-2320	2175-2320	2320-2460