



RAYCO

BY MORBARK

The **Super Jr** stump cutter is the original self-propelled, backyard stump cutter that professionals have relied on since 1986. Today, there's a Super Jr model to fit every job and every budget. To maximize visibility while cutting, all Super Jr's have the drivetrain located on the far side of the cutter wheel. And Rayco's exclusive, swing-out control station gives operators the best view while cutting and swings in-line with the machine for travel through gates. Wide, flotation tires with bar tread give the Super Jr a firm grip on the terrain, and dual wheels can be added for extra stability. Rayco's exclusive slewing ring pivot design lowers the center of gravity and lets the Super Jr cut at maximum depth across the whole swing path.



MADE FOR **MORE** TO KEEP PACE WITH **YOU**

RG37 SUPER Jr

FEATURES AND BENEFITS

- Slewing ring pivot design increases cutting width
- Full cutting depth across entire width of cut
- Lower center of gravity
- Wide tires for enhanced traction and flotation
- Swing-out operator station
- Controls swing in line for travel through gates
- Gasoline engines with heavy duty air filter
- 37-hp Vanguard engine
- Centrifugal precleaner
- Hydraulic backfill blade
- Two speed ground travel
- Optional dual rear wheels & Command Cut
- Optional 4-Wheel drive



MORBARKDEALERS.COM



MORBARK



RAYCO RG37 SUPER Jr SPECIFICATIONS

BY MORBARK®

General	US	Metric
Weight	1,830 lb	831 kg
Length	114"	290 cm
Height	52"	132 cm
Width	35"	89 cm
Width with Dual Wheels (Maximum)	52.5"	133 cm
Ground Drive	2 Speed	
Tires	18 x 8.5-10 R4 4-ply	
Backfill Blade	Standard	
Engine	37-hp Vanguard	27.6-kW Vanguard
Fuel Type	Gasoline	Petrol
Maximum Rated Torque	51 ft-lb at 2500 RPM	69.5 Nm at 2500 RPM
Fuel Tank Capacity	5 gallon	18.9 L
Electrical System	12 volts/15 AMP alternator	
Oil Tank Capacity	2 gallon	7.6 L
Cutting Wheel Diameter	17.25"	43.8 cm
Cutting Wheel Thickness	1"	2.5 cm
Cutting Wheel Bearings	1.5" Pillow Block Type	3.81 cm Pillow Block Type
Super Tooth®	18 Total	
Clutch	Electromagnetic with "Quick Stop" Brake System	
Cutting Depth	12"	30 cm
Cutting Height	24.5"	62.2 cm
Cutting Width	51"	130 cm



Swing out control station for better visibility. Controls fold in line for travel through gates.



51-inch cutting width for full cutting depth across entire width of cut.



Hydraulic backfill blade for quick and easy clean up.

